

9180

PERFORMANS TABLOSU / PERFORMANCE CHART

Pompa Tipi PumpType	Güç Power	Güç Power	Q m ³ /h	126	135	144	153	162	171	180	189	198	207	216	225	234
	HP	kW	Q lt/sec	35	37,5	40,0	42,5	45	47,5	50,0	52,5	55	57,5	60	62,5	65
9180 / 02B	40	30	MMS (m)	55	53	52	50	48	46	44	42	40	32	24	-	-
9180 / 02A	50	37		58	57	56	54	53	52	50	48	47	45	43	41	37
9180 / 03B	60	45		82	80	78	75	72	71	66	63	60	48	46	-	-
9180 / 03A	75	55		88	86	84	82	80	78	75	73	70	67	65	61	57
9180 / 04A	100	75		117	114	112	109	107	104	100	97	94	90	86	82	76
9180 / 05A	125	92		146	143	140	136	133	130	125	121	117	112	107	102	95
9180 / 06A	150	110		176	171	168	163	160	156	150	146	141	135	129	123	114
9180 / 07A	175	129		205	200	196	191	187	182	175	170	164	157	150	143	123

ÖLÇÜ TABLOSU / DIMENSIONS CHART

Pompa Tipi PumpType	Güç Power	Güç Power	Motor Tipi Motor Type	Ø=D	Q=A	Q=E	Pompa Uzunluğu Pump Length	Pompa Ağırlığı Pump Weight
	HP	kW			mm	mm	LA (mm)	Kg
9180 / 02B	40	30	8"	6"	230	232	929	86
9180 / 02A	50	37					929	86
9180 / 03B	60	45					1094	112
9180 / 03A	75	55					1094	112
9180 / 04A	100	75	8" 10"				1259	138
9180 / 05A	125	92					1424	164
9180 / 06A	150	110	10"				1589	190
9180 / 07A	175	129					1754	216

ÜRÜN ÖZELLİKLERİ			PRODUCT SPECIFICATIONS		
Ara Çanak	Pik Döküm	GG20	Intermediate Bowl	Stainless Steel	GG20
Fan	Pik Döküm	GG20	Impeller	Stainless Steel	GG20
Pompa Mili	Paslanmaz Çelik	AISI 420	Pump Shaft	Stainless Steel	AISI 420
Kaplin	Paslanmaz Çelik	AISI 420	Coupling	Stainless Steel	AISI 420
Filtre & Kablo Kanalı	Paslanmaz Çelik	AISI 420	Filter & Cable Guard	Stainless Steel	AISI 420
Klepe	Paslanmaz Çelik	AISI 420	Valve Cap	Stainless Steel	AISI 420



